










ARWEI-PREMIUM-REINSTREIFER DATA SHEET PORTAL KLASSIKER 22



-  High collection volume up to 7,9 litres per m²
-  Interior
-  Suitable for wheelchairs
-  Rinsing
-  Rollable


Recommended for:

-  Private Homes
-  Office buildings
-  Kindergartens
-  Schools
-  Hospitals
-  Shopping centres
-  Public and fairground halls

Height	Bar distance	Profile	Walking Area	Weight per m ²
22 mm	3 / 5 mm	Plastic	Needle felt	approx. 9,0 kg (with 5 mm bar spacing)

System Design

- 1 Needle felt
- 2 Plastic Profile
- 3 ARWEI special connector, without cable connections




Characteristics

- V-profile form with increased solid dirt collection of 7,9 litres per m²
- Special needle felt - extremely wear-resistance, long life time, 4-5 mm compact fabric top layer
- The ARWEI "Special Needle Felt" is certified "TÜV PROFICERT-product Interior PREMIUM"

Advantages

- ARWEI-Premium-Reinstreifer is manufactured as a modular system. Every single part can be replaced easily on the spot.
- ARWEI needle felt convinces with an excellent cleaning effect, a duplicated life time versus conventional sling ware, a minimum of getting dirty itself and a high wear-resistance. 4-5 mm compact fabric top layer.
- The needle felt is fixed with a screw to prevent slipping sideways.
- The special profile geometry of the ARWEI Reinstreifer allows for high strain, for example for driving over with wheel chairs.
- The ARWEI "Special Needle Felt" is certified "TÜV PROFICERT-product Interior PREMIUM" and is therewith a proven product for emission requirements by DGNB for the criteria „ENV1.2 risks for local environment“.

Standard Colours



Special Colours (Available at an extra charge)




Illustration of colors not true to original.
On request you receive original samples promptly.

Tender specifications: Portal Klassiker 22

High quality, especially wear-resistant entrance mat

Application: Indoor; for warmth up to 45°C; normal up to extremely strong frequency, suitable for trolleys and wheelchairs, overall laying

Stripe profile: Plastic, anthracite, V-shaped; 3 mm ground clearance, uncoupled, sound insulated, rinsing, rear ventilated

Needle felt special ground: 100 % PP; pole density 2400 g / m²; completely needled; no sling ware, minimum contamination; extremely wear-resistant; is fixed in a covered manner to prevent slipping sideways; needle felt can be substituted subsequently; colours anthracite, light grey, grey blue; coconut, special colours on demand; slip resistance R 11 according to DIN 51130

ARWEI "Special Needle Felt" is certified "TÜV PROFiCERT-product Interior PREMIUM"

AgBB; A+ (Émissions dans l'air intérieur); Belgian VOC-regulation; LEED v4 (outside North America); BREEAM Exemplary Level; Finnish M1-Klassifizierung; GUT / PRODIS; DE-UZ 128 (Blue Angel); EU-Ecolabel; Austrich env. label UZ 35; CAM Italy; MVV TB Anhang 8+9 / ABG



Colour fastness

Rubbing fastness (DIN EN ISO 105-X12) dry: Grade: 3-4 (good) wet: 4-5 (very good)

Water fastness (DIN EN ISO 105-E01) Grade: 4-5 (very good)

Light fastness (DIN EN ISO 105-B02) Grade: 7 (good)

Connection: ARWEI Special Connectors (patented in 1977); therefore easily to roll up, modular construction – no wire or cable connections -, each part can easily be replaced on the spot

Height: 22 mm

Bar distance 3 mm: Coarse dirt absorption 6,9 l / m²

Bar distance 5 mm: Coarse dirt absorption 7,9 l / m²

Angle frames in 25 x 25 x 3 mm are available in aluminum, brass or stainless steel.