

PUREDESIGN BY ARWEI®

ARWEI-PREMIUM-REINSTREIFER DATA SHEET PORTAL SCB 42





Static point loading up to 12,6 t per 80 cm²



Interior and roofed exterior

Suitable for heavy load



Exterior



Suitable for wheelchairs



Coarse dirt absorption



Rollable





Office buildings



Schools



Hospitals



Shopping centres



Public and fairground halls


Height	Bar distance	Profile	Walking Area	Weight per m ²
42 mm	4 / 6 mm	Aluminum	Cassette Brush	approx. 27,2 kg (with 6 mm bar spacing)

System Design

- ARWEI-Cassette Brush
- 2 Aluminum profile
- 3 ARWEI special connector, without cable connections
- 4 Scratching Edge

Characteristics

Extremly high stability up to 12600 kg per 80 cm² static point load



Advantages

- ARWEI-Premium-Reinstreifer is manufactured as a modular system. Every single part can be replaced easily on the spot.
- The cassette brushes are fixed in a covered manner to prevent slipping sideways.
- The special profile geometry of the ARWEI Pure Design enables a high strain. The Reinstreifer is drivable.



PUREDESIGN BY ARWEI®

Tender specifications: Portal SCB 42

High quality, especially wear-resistant entrance mat

Application: Indoor and roofed exterior; normal up to extremely strong frequency, drivable for trolleys, pallet trucks, cars, etc.; suitable for wheelchairs, overall laying, Static point loading up to 12600 kg per 80 cm²

Stripe profile: aluminum, with scratching edge, sound insulated

Cassette brush: with bristle bundles arranged parallel to one another, colour black, slip resistance R 12 according to DIN 51130

Connection: ARWEI Special Connectors; therefore easily to roll up, high slip resistance by anti-slip function; modular construction – no wire or cable connections -, each part can easily be replaced on the spot

Height: 42 mm

Bar distance: 4 or 6 mm

At a bar distance of 3 mm also appropriate for automatically revolving doors according to DIN 18650-1.

Angle frames in 45 x 25 x 3 mm are available in aluminum, brass or stainless steel.



ARWEI REINSTREIFER IN ACTION.

www.youtube.com/arweitv





Constructional and material changes in the course of further product development reserved. All dimensions are standard values without considering production engineering-related tolerances. They are based on our experience and testing. The variety of associated materials and working conditions that occur on jobsites are not checked in detail and cannot be influenced by us. The quality of your work depends on your own professional judgment and product usage. If in doubt of any application recommendation or instruction, conduct a small test or obtain technical advice. With the publication of this product data sheet invalidates all previous product information. The respective updated version of this datasheet can be found on our Homepage under www.arwei.de.