CLEAN IDEAS WITH SYSTEM

PUREDESIGN BY ARWEI®



ARWEI-PREMIUM-REINSTREIFER

DATA SHEET PORTAL SN 12

Static point loading up to 6,5 t per 80 cm²

Interior and roofed exterior

Suitable for wheelchairs

Suitable for heavy load

Rollable

Recommended for:

Private Homes

Office buildings

Kindergartens

Schools

Hospitals

Shopping centres

Public and fairground halls

Height	Bar distance	Profile	Walking Area	Weight per m²
12 mm	4 / 6 mm	Aluminum	Needle felt	approx. 10,2 kg (with 6 mm bar spacing)

System Design



1. Needle felt
2. Aluminum profile
3. ARWEI special connector, without cable connections
4. Scratching Edge

Characteristics

- Extreme high stability up to 6500 kg per 80 cm² static point load

Advantages

- ARWEI-Premium-Reinstreifer is manufactured as a modular system.
  Every single part can be replaced easily on the spot.
- The special profile geometry of the ARWEI Reinstreifer allows for high strain. The Reinstreifer is drivable.

Standard Colours



anthracite | light grey | beige brown | blue | red | green

Illustration of colors not true to original.
On request you receive original samples promptly.

Tender specifications: Portal SN 12

High quality, especially wear-resistant entrance mat

Application: Indoor and roofed exterior; normal up to extremely strong frequency, drivable for trolleys, pallet trucks, cars, etc.; suitable for wheelchairs, overall laying, Static point loading up to 10000 kg per 80 cm²

Stripe profile: aluminum, with scratching edge, sound insulated

Needle felt special ground: completely needled; no sling ware, minimum contamination; extremely wear-resistant; is fixed in a covered manner to prevent slipping sideways; needle felt can be substituted subsequently; slip resistance R 11 according to DIN 51130

Colour fastness
Rubbing fastness (DIN EN ISO 105-X12) dry: Grade: 3-4 (good) wet: 4-5 (very good)
Water fastness (DIN EN ISO 105-E01) Grade: 4-5 (very good)
Light fastness (DIN EN ISO 105-B02) Grade: 7 (good)

Connection: ARWEI Special Connectors; therefore easily to roll up, high slip resistance by anti-slip function; modular construction – no wire or cable connections -, each part can easily be replaced on the spot

Height:	12 mm
Bar distance:	4 or 6 mm

Mitglied der DGNB

TÜVNORD TÜV NORD CERT GmbH DIN EN ISO 9001 tuev-nord.de

MADE IN GERMANY

Constructional and material changes in the course of further product development reserved. All dimensions are standard values without considering production engineering-related tolerances. They are based on our experience and testing. The variety of associated materials and working conditions that occur on jobsites are not checked in detail and cannot be influenced by us. The quality of your work depends on your own professional judgment and product usage. If in doubt of any application recommendation or instruction, conduct a small test or obtain technical advice. With the publication of this product data sheet invalidates all previous product information. The respective updated version of this datasheet can be found on our Homepage under www.arwei.de.

ARWEI-Bauzubehör GmbH | Kalteiche-Ring 48 | D-35708 Haiger | Tel.: +49 (0) 2773 91788-0 | Fax: +49 (0) 2773 91788-50 | eMail: info@arwei.de www.arwei.de

Stand 12.2025